




SPECIFICATION SHEET

MODELS 741BRC, 741SNC, & 741WHC DESIGNER VENTILATION FAN /LIGHT



A powerful ventilating fan with the look of an elegant glass light fixture.

FEATURES

LIGHT FIXTURE:

- Corrosion-resistant finish
 - Polished brass finish Model 741BRC
 - Satin nickel finish Model 741SNC
 - Gloss white finish Model 741WHC
- Frosted melon glass shade
- Close mount design
- Uses two 60W maximum, type A, medium base bulbs Models 741BRC, 741SNC & 741WHC. Bulbs not included
- Vent openings in fixture base for exhaust fan
- Light fixture assembly is plug-in and removable

BLOWER:

- Plug-in permanently lubricated motor
- Polymeric blower wheel

HOUSING:

- Rugged, 26-gauge galvanized steel construction
- Sturdy key-holed mounting brackets for quick, accurate installation
- Tapered 4" (101.6 mm), polymeric duct fitting with built-in backdraft damper for easy, positive duct connection and no metallic clatter

NOTE: For installation in ceilings up to 12/12 pitch. Use supply wiring rated for at least 90° C

TYPICAL SPECIFICATION

Decorative Light/Fan unit shall be Broan Model 741BRC, 741SNC or 741WHC.


Unit shall have galvanized steel housing with dual integral mounting brackets. It shall be ducted through a roof or wall cap. Blower assembly shall be removable and have a permanently lubricated motor.

Light fixture assembly shall be plug-in, removable and include a frosted melon glass shade and a corrosion-resistant base with polished brass Model 741BRC, satin nickel Model 741SNC & painted white Model 741WHC finish. Lamps shall be two 60W maximum, type A, medium base, incandescent Models 741BRC, 741SNC & 741WHC. Units are Type I.C. inherently protected.


Air delivery to be no less than 70 CFM (33.0 L/s) and sound level no greater than 3.5 sones. Air and sound ratings shall be certified by HVI. Units shall be cULus listed.

SPECIFICATIONS

MODEL	VOLTS	AMPS	SONES	CFM (L/s)	Duct (Round)
741BRC	120	2.2	3.5	70 (33.0)	4" (101.6mm)
741SNC	120	2.2	3.5	70 (33.0)	4" (101.6mm)
741WHC	120	2.2	3.5	70 (33.0)	4" (101.6mm)



HVI-2100 CERTIFIED RATINGS comply with the new testing technologies and procedures prescribed by the Home Ventilation Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 in. static pressure, based on tests conducted in AMCA's state-of-the-art laboratory. Sones are a measure of humanly produced loudness, based on laboratory measurements.



Broan-NuTone LLC, Hartford, Wisconsin, U.S.A. 53027
Broan-NuTone Canada Inc., Mississauga, Ontario, Canada L5T 1H9

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date